

Micro-Burettes, Hirschmann

Micro-burettes acc. to Bang with straight stopcock, glass key with standard ground joint size 12

Stopcock at the filling tube with glass key, with dated batch identification, class AS, with declaration of conformity acc. to DIN 12600, main point ring graduation, DURAN®, with Schellbachline, acc. to DIN EN ISO 385. Graduation and printing in blue durable ceramic stain.

Volume ml	Graduation ml	Tol. ± ml	Flow time s	Order No.	PU pc/Pack
2	0.01	0.01	8 – 20	14 81 48134	2
① 5	0.02	0.01	15 – 25	14 81 48146	2
10 ¹⁾	0.02	0.02	35 – 45	14 81 48156	2

¹⁾ In addition to DIN size

Waiting time 30 s

Micro-burettes acc. to Bang with straight stopcock with PTFE key with standard ground joint size 12

Stopcock at the filling tube with PTFE key joint size 12, with dated batch identification, class AS, with declaration of conformity acc. to DIN 12600, acc. to DIN EN ISO 385. Graduation and printing in blue durable ceramic stain, with Schellbachline.

Volume ml	Graduation ml	Tol. ± ml	Flow time s	Order No.	PU pc/Pack
2	0.01	0.01	8 – 20	14 81 48234	2
5	0.02	0.01	15 – 25	14 81 48246	2
10 ¹⁾	0.02	0.02	35 – 45	14 81 48256	2

¹⁾ In addition to DIN size

Waiting time 30 s



HIRSCHMANN®

webcode  **WW4ZV027**

